



Refractory Lining Demolition

Refractory linings demolished with ease and in complete safety.

Our new remotely controlled machines can be used for many different demolition processes within the refractory industry.



Technical Data

Brokk 50

Transport Length (exc.attachments) 1380mm
 Transport Height 940mm
 Transport Width 600mm
 Working Radius 2400mm
 Weight (exc. Attachments) 475kgs
 Electrical Connection 415 volt x 16 Amp Supply

Brokk 90

Transport Length (exc.attachments) 1600mm
 Transport Height 1285mm
 Transport Width 780mm
 Working Radius 3000mm
 Weight (exc. Attachments) 980Kgs
 Electrical Connection 415 volt x 32 Amp Supply

Brokk 150C

Transport Length (exc.attachments) 2340mm
 Transport Height 1245mm
 Transport Width 1130mm
 Working Radius 3500mm
 Weight (exc. Attachments) 1750Kgs
 Electrical Connection 415 volt x 63 Amp Supply

Brokk 180

Transport Length (exc.attachments) 2489mm
 Transport Height 1392mm
 Transport Width 1200mm
 Working Radius 4000mm
 Weight (exc. Attachments) 1930Kgs
 Electrical Connection 415 volt x 63 Amp Supply



S.H.L. Refractories (UK) Ltd

Celcius House, Lawn Road Industrial Estate,
 Carlton-in-Lindrick, Worksop, Nottinghamshire S81 9LB

T: 01909 731959 F: 01909 731579

E: sales@shl-refractories.co.uk www.shl-refractories.co.uk

